



TP171A

7.5W class II adapter, single phase, single output power supply.



Model ref: TPSF-7.5-1-A

OVERVIEW

- 7.5W Power supply

APPLICATION

- Class II adapter

INPUT

- Universal input voltage range : 90-264Vac
- Leakage current : 0.25 mA RMS max
- Efficiency : > 75%
- Class II

OUTPUT

- Nominal output power : 7.5W
- Single output voltage : +5Vdc
: Other voltages upon request

PROTECTIONS

- Overload / short circuit protection
- Fuse protected AC input

CERTIFICATES

- UL



SAFETY & EMC

- IEC/EN/UL 60950-1
- IEC/EN 61000-4-2
- IEC/EN 61000-4-3
- IEC/EN 61000-4-4
- IEC/EN 61000-4-5

COOLING

- Free air convection

CONSTRUCTION

- Adapter housing

CONNECTIONS

- Input : Interchangeable AC connector, with SAA, EU, UK and US plug
- Output : DC plug 5.5x2.1x9.5mm
 - : USB-C
 - : Other configurations upon request

DIMENSIONS & WEIGHT

- Dimensions (L X W X H) : 79 x 41 x 40 mm
 - : 3.1 x 1.6 x 1.6 inch
- Weight : 0.1 KG